

CHEROKEE COUNTY DRIVEWAY ACCESS

**IT IS THE RESPONSIBILITY OF THE PROPERTY OWNER/CONTRACTOR TO
INSTALL THE DRIVEWAY IN ACCORDANCE WITH THE FOLLOWING
SPECIFICATIONS:**

- 1. Property owner/contractor must place stakes 24 feet (according to SC DOT) apart where access is requested. This will allow the inspector to inspect the site for pipe size. Please remember that the proposed entrance must have good visibility in each direction.**
- 2. The Cherokee county Public Works Director or his agent will inspect the site and determine the pipe size. This information will then be forwarded to the Building Codes Department. All questions concerning pipe size should be addressed to Building Codes.**
- 3. Poly pipe may be used. Twenty four feet is the standard width for residential access.**
- 4. The pipe must be installed straight and joints must be sealed by manufacturer's specifications. The backfill must be compacted and a 6 inch crusher run base placed and compacted over the pipe.**
- 5. Installed asphalt or concrete aprons (optional) are the responsibility of the property owner/contractor. Asphalt aprons should be 2 inches compacted (150 lbs. Per square yard). Concrete aprons may be substituted on roads with curb and gutter and should be 4 inches (minimum) for residential. Commercial driveway thickness will vary depending on conditions.**
- 6. Driveway entrance must be installed and approved by the Building codes inspector along with electrical, plumbing etc. prior to final inspection being approved.**